

Technical data Multi-turn actuators for modulating duty with 3-phase AC motor

**General information**  
 AUMA TR-M30X – TR-M1000X multi-turn actuators with integral controls for valve automation in potentially explosive atmospheres.

Type	Output speed rpm		Torque range <sup>1)</sup>			Modulating torque <sup>2)</sup>		Number of starts	Pulse duration <sup>3)</sup>	Pulse duration on reversal <sup>4)</sup>	Valve attachment <sup>5)</sup>			Handwheel		Weight <sup>6)</sup>
	50 Hz	60 Hz	Min. [Nm]	S4 - 25% Max. [Nm]	S4 - 50% Max. [Nm]	S4 - 25% Max. [Nm]	S4 - 50% Max. [Nm]				Starts Max. [1/h]	Min. [ms]	Max. [ms]	Standard EN ISO 5210	Option DIN 3210	
TR-M 30X	4	4.8	10	30	20	15	8	1,200	50	260	F07 F10	-	26 34	160	11:1	26
	5.6	6.7								200					8:1	
	8	9.6								155					11:1	
	11	13								130					8:1	
	16	19								100					11:1	
	22	26								90					8:1	
	32	38								75					11:1	
	45	54								70					8:1	
60X	4	4.8	10	60	40	30	15	1,200	50	260	F07 F10	-	26 34	160	11:1	27
	5.6	6.7								200					8:1	
	8	9.6								155					11:1	
	11	13								130					8:1	
	16	19								100					11:1	
	22	26								90					8:1	
	32	38								75					11:1	
	45	54								70					8:1	
120X	4	4.8	12	120	90	60	30	1,000	50	260	F10	G0	40	200	11:1	30
	5.6	6.7								200					8:1	
	8	9.6								155					11:1	
	11	13								130					8:1	
	16	19								100					11:1	
	22	26								90					8:1	
	32	38								75					11:1	
	45	54								70					8:1	
250X	4	4.8	25	250	180	120	60	900	70	280	F14	G1/2	58	315	11:1	48
	5.6	6.7						220		8:1						
	8	9.6						175		11:1						
	11	13						150		8:1						
	16	19						120		11:1						
	22	26						110		8:1						
	32	38						100		11:1						
	45	54						90		8:1						
500X	4	4.8	50	500	360	200	100	600	70	280	F14	G1/2	58	315	45:1	50
	5.6	6.7								220					33:1	
	8	9.6								175					45:1	
	11	13								150					33:1	
	16	19				120	45:1									
	22	26				110	33:1									
	32	38				100	45:1									
	45	54				90	33:1									
1000X	4	4.8	100	1,000	710	330	170	600	100	300	F16	G3	77	315	45:1	66
	5.6	6.7								250					33:1	
	8	9.6								200					45:1	
	11	13								175					33:1	
	16	19				150	45:1									
	22	26				140	33:1									
	32	38				130	45:1									
	45	54				120	33:1									

- 1) The tripping torque is adjustable for directions OPEN and CLOSE within the indicated torque range.
- 2) Maximum permissible torque for modulating duty
- 3) For identical direction of rotation: time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 4) For reversal of direction of rotation: time duration for which the motor must be electrically powered until there is a movement at the output drive.
- 5) Indicated flange sizes apply for output drive types A and B1.
- 6) Indicated weight includes multi-turn actuator with 3-phase AC motor, electrical connection in standard version, output drive type B1 and handwheel.

We reserve the right to alter data according to improvements made. Previous documents become invalid with the issue of this document. For further information on the product, refer to [www.auma.com](http://www.auma.com).

## Technical data Multi-turn actuators for modulating duty with 3-phase AC motor

Features and functions											
Explosion protection	Standard: II2G Ex db eb h IIC T4 or T3 Gb II2D Ex tb h IIC T 130°C or T 190°C Db										
	Options: II2G Ex db h IIC T4 or T3 Gb										
Product certificates	DEKRA 19 ATEX 0091 X IECEX DEK 19.0055 X										
Type of duty	Standard: Intermittent duty S4 - 25 %, class C according to EN 15714-2										
	Option: Intermittent duty S4 - 50 %, class C according to EN 15714-2										
	For nominal voltage and +40 °C ambient temperature and at modulating torque load.										
Motors	3-phase AC asynchronous squirrel-cage motor, type IM B9 according to IEC 60034-7, IC410 cooling procedure according to IEC 60034-6										
Mains voltage, mains frequency	Standard voltages:										
	3-phase AC Voltages/frequencies										
	Volt	380	380	400	400	415	440	440	460	480	500
	Hz	50	60	50	60	50	50	60	60	60	50
	Special voltages:										
	3-phase AC Voltages/frequencies										
	Volt	220	220	230	525	575	600	660			
Hz	50	60	50	50	60	60	50				
Further voltages on request	Permissible variation of mains voltage: ±10 % Permissible variation of mains frequency: ±5 %										
Overvoltage category	Category III according to IEC 60364-4-443										
Insulation class	Standard: F, tropicalized										
	Option: H, tropicalized										
Motor protection	PTC thermistors (according to DIN 44082)										
Self-locking	Yes, multi-turn actuators are self-locking, if the valve position cannot be changed from standstill while torque acts upon the output drive.										
Motor heater (option)	Voltages: 110 – 120 V AC, 220 – 240 V AC or 380 – 480 V AC										
	Power depending on the size 12.5 – 25 W										
Manual operation	Manual drive for setting and emergency operation, handwheel does not rotate during electrical operation										
	Options: Handwheel lockable Handwheel stem extension Power tool for emergency operation with square 30 mm or 50 mm										
Indication for manual operation (option)	Signal for manual operation active/not active										
Electrical connection	Standard: AUMA Ex plug/socket connector (KT, KM), screw-type motor terminals, push-in type control terminals										
	Option: AUMA Ex plug/socket connector (KT, KM), with additional support terminals in plug/socket connector										
Threads for cable entries	Standard: Metric threads										
	Options: NPT threads, G threads										
Valve attachment	Standard: B1 according to EN ISO 5210										
	Options: A, B2, B3, B4, C, D according to EN ISO 5210 A, B, D, E according to DIN 3210 C according to DIN 3338										
	Special valve attachments: AF, AK, AG, B3D, ED, DD, IB1, IB3, A prepared for permanent lubrication of stem										
Position sensing	Absolute encoder, magnetic for position sensing (MWG) Turns per stroke: 2 to 500 (standard) or 20 to 5,000 (option)										

## Technical data Multi-turn actuators for modulating duty with 3-phase AC motor

Features and functions	
Torque sensing	AUMA torque sensor; resolution $\pm 2\%$ , referring to maximum adjustable torque.
External supply of the electronics (option)	24 V DC: $+20\%/ -15\%$ For external electronics supply, the power supply of integral controls must have an enhanced isolation against mains voltage in compliance with IEC 61010-1 and the output power be limited to 150 VA.
Rated power	The rated power is the nominal motor power, refer to Electrical data.
Switchgear	Standard: Reversing contactors (mechanically and electrically interlocked) for AUMA power classes A1 and A2
	Options: Thyristor unit for mains voltage up to 500 V AC for AUMA power classes B1, B2 and B3
	For the assignment of AUMA power classes, please refer to Electrical data.
Digital input	Standard: 4 digital inputs: OPEN, STOP, CLOSE, EMERGENCY (via opto-coupler with one common).
	Option: 6 digital inputs, e.g. OPEN, STOP, CLOSE, EMERGENCY, MODE, Enable LOCAL
Analogue input	With positioner option: Input of actuator position setpoint as continuous value from 0/4 – 20 mA
Control voltage/current consumption for digital control inputs	Standard: 24 V DC, current consumption: approx. 10 mA per input
	All input signals must be supplied with the same potential.
Status signals (output signals)	Standard: <ul style="list-style-type: none"> <li>6 programmable output contacts: <ul style="list-style-type: none"> <li>5 potential-free NO contacts with one common, max. 250 V AC, 1 A (resistive load)</li> <li>1 potential-free change-over contact, max. 250 V AC, 5 A (resistive load)</li> </ul> </li> <li>Analogue output signal for position feedback <ul style="list-style-type: none"> <li>Galvanically isolated position feedback 0/4 – 20 mA (load max. 500 Ohm)</li> </ul> </li> </ul>
	Options: <ul style="list-style-type: none"> <li>6 programmable output contacts: <ul style="list-style-type: none"> <li>5 change-over contacts with separate common, max. 250 V AC, 1 A (resistive load), 1 potential-free change-over contact, max. 250 V AC, 5 A (resistive load)</li> </ul> </li> <li>1 further analogue output, e.g. torque output as continuous value from 0/4 – 20 mA</li> </ul>
Voltage output	Standard: Auxiliary voltage 24 V DC: max. 100 mA for supply of control inputs, galvanically isolated from internal voltage supply.
	Option: Auxiliary voltage 115 V AC: max. 30 mA for supply of control inputs, galvanically isolated from internal voltage supply
Local controls	Standard: <ul style="list-style-type: none"> <li>Combi-Switch with the following functions: <ul style="list-style-type: none"> <li>Selector switch: LOCAL-OFF-REMOTE, ESC, ENTER, (RESET)</li> <li>Shuttle dial: OPEN, CLOSE, (STOP)</li> </ul> </li> <li>Selector switch: lockable in all three positions</li> <li>6 indication lights: <ul style="list-style-type: none"> <li>End position and running indication OPEN (green), torque fault OPEN (red), motor protection tripped (red), torque fault CLOSE (red), end position and running indication CLOSE (yellow), Bluetooth communication (blue)</li> </ul> </li> <li>Graphic LC display: illuminated For display of all essential actuator data like travel position, torque, type of seating, etc.</li> </ul>
	Option: <ul style="list-style-type: none"> <li>Colours and functions of indication lights to be selected via the menu according to operation instructions</li> </ul>
Bluetooth module	Deactivation/activation from remote
Application functions	Standard: <ul style="list-style-type: none"> <li>Type of seating: limit or torque seating respectively for end positions OPEN and CLOSED</li> <li>Torque by-pass</li> <li>Stepping mode</li> <li>Any 8 intermediate positions: can be set between 0 and 100 %, reaction and signal behaviour programmable</li> <li>Running indication blinking: adjustable</li> </ul>
	Options: <ul style="list-style-type: none"> <li>Positioner: <ul style="list-style-type: none"> <li>Position setpoint via analogue input 0/4 – 20 mA</li> <li>Programmable behaviour on loss of signal</li> <li>Automatic adaptation of dead band (adaptive behaviour selectable)</li> <li>Split range operation</li> <li>MODE input for selecting between OPEN-CLOSE and setpoint control</li> </ul> </li> </ul>

## Technical data Multi-turn actuators for modulating duty with 3-phase AC motor

Features and functions	
Safety functions	Standard: <ul style="list-style-type: none"> <li>EMERGENCY operation (behaviour to be selected)               <ul style="list-style-type: none"> <li>- Tripping: Digital input: Low active</li> <li>- Reaction: Stop, end position CLOSED, end position OPEN, setpoint position</li> <li>- Torque monitoring can be by-passed during EMERGENCY operation</li> </ul> </li> </ul>
	Options: <ul style="list-style-type: none"> <li>Enabling local controls via digital input "Enable LOCAL": Actuator operation via local controls can be enabled or disabled</li> <li>Interlock function: Enabling the operation commands OPEN or CLOSE from Remote via two digital inputs</li> <li>PST (Partial Stroke Test): Programmable to check the function of the actuator</li> </ul>
Monitoring function	<ul style="list-style-type: none"> <li>Valve overload protection: Torque limit value adjustable, results in switching off and generates fault signal</li> <li>Motor temperature monitoring: results in switching off and generates fault signal</li> <li>Monitoring the heater within actuator (if available): generates warning signal</li> <li>Monitoring of permissible operation mode: adjustable, generates warning signal</li> <li>Operation time monitoring: adjustable, generates warning signal</li> <li>Phase failure monitoring: results in switching off and generates fault signal</li> <li>Rotary direction monitoring: results in switching off and generates fault signal</li> </ul>
Diagnostic function	<ul style="list-style-type: none"> <li>Electronic device ID with order and product data</li> <li>Logging of operating data: A resettable counter and a lifetime counter each for:               <ul style="list-style-type: none"> <li>- e.g. motor running time, number of starts, torque switch trippings in end position CLOSED, limit switch trippings in end position CLOSED, torque switch trippings in end position OPEN, limit switch trippings in end position OPEN, torque faults CLOSE, torque faults OPEN, motor protection trippings</li> </ul> </li> <li>Time-stamped event report with history for setting, operation and faults</li> <li>Status signals according to NAMUR recommendation NE 107: "Failure", "Function check", "Out of specification", "Maintenance required"</li> <li>Torque profile:               <ul style="list-style-type: none"> <li>- Various reference operations can be executed (e.g. for commissioning)</li> <li>- Torque values can be stored as reference profile.</li> <li>- Comparison operation can be executed at any time (e.g. for plant control).</li> <li>- Tolerance values can be flexibly defined for travel.</li> <li>- Values outside the permissible range generate configurable signals to the DCS.</li> </ul> </li> </ul>
Wiring diagram (basic version)	TPC T-0A1AAB11-000
Service conditions	
Use	Indoor and outdoor use permissible
Mounting position	Any position
Installation altitude	≤ 2,000 m above sea level
	> 2 000 m above sea level on request
Ambient temperature	Standard: -30 °C to +60°C
	Options: <ul style="list-style-type: none"> <li>-30 °C to +70°C</li> <li>-40 °C to +60 °C</li> <li>-50 °C to +60 °C (on request)</li> <li>-65 °C to +60 °C (on request)</li> </ul>
	For ambient temperatures ≤ -40 °C including heater or heating system
Humidity	Up to 100 % relative humidity across the entire permissible temperature range
Enclosure protection in accordance with IEC 60529	IP68 with AUMA 3-phase AC motor Terminal compartment additionally sealed against interior of actuator (double sealed)
	According to AUMA definition, enclosure protection IP68 meets the following requirements: <ul style="list-style-type: none"> <li>Depth of water: maximum 8 m head of water</li> <li>Continuous immersion in water: maximal 96 hours</li> <li>Up to 10 operations during immersion</li> <li>Modulating duty is not possible during immersion.</li> </ul>
Pollution degree according to IEC 60664-1	Pollution degree 4 (when closed), pollution degree 2 (internal)

### Technical data Multi-turn actuators for modulating duty with 3-phase AC motor

Vibration resistance according to IEC 60068-2-6	2 g, 5 to 200 Hz Resistant up to maximum 2g to vibration during start-up or for failures of the plant. Resistance against frequent or continuously occurring vibration cannot be derived from this. Not valid in combination with gearboxes. Detailed information on request.	
Corrosion protection	Standard:	KS: Suitable for use in areas with high salinity, almost permanent condensation, and high pollution.
	Options:	KX: Suitable for use in areas with extremely high salinity, permanent condensation, and high pollution.
Coating	Double layer powder coating	
Colour	Standard:	AUMA silver-grey (similar to RAL 7037)
	Options:	Available colours on request
Lifetime	AUMA multi-turn actuators meet or exceed the lifetime requirements of EN 15714-2. Detailed information can be provided on request.	
Sound pressure level	< 72 dB (A)	

#### Accessories

Wall mount controls (wall mounted version)	Wall mount controls including local controls separately mounted from actuator, connecting cables on request. Recommended when difficult to access or heavy operational vibration occurring on site. Cable length between actuator and separately mounted local controls amounts to max. 100 m.
Software tool (via Bluetooth connection)	AUMA CDT (Commissioning and Diagnostic Tool for Windows-based PC/notebook)

#### Further information

EU Directives	ATEX Directive 2014/34/EU Machinery Directive 2006/42/EC Low Voltage Directive 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU
Reference documents	Dimensions Multi-turn actuators TR-M30X – TR-M1000X Electrical data Multi-turn actuators TR-M30X – TR-M1000X