



PRODUCT PART NUMBER →			V-690SCT
ITEM	DESCRIPTION	PRESS. TEMP. →	10,000 PSI @ 200° F MIN. 8,000 PSI @ 450° F MAX.
1	Body	(S)	ASTM A479-316
2	Ball Seat (3)	(C)	CARBIDE BALL
3	Stem Seal (3)	(T)	TEFLON PRESSURE CORE
4	Stem (3)		ASTM 479-316
5	Bonnet (3)		ASTM 479-316
6	Handle Assembly (3)		ASTM A582 18-8
7	Seal Retainer (3)		ASTM 479-316

NOTES

1. DIMENSIONS IN [] ARE IN MILLIMETERS.
2. APPROX. WEIGHT 3.7 lbs. (1.51 kg.)
3. <ZC> INDICATES ZINC COBALT PLATED WITH DICHROMATE DIP.
4. <P0> INDICATES PHOSPHATE AND OIL.
5. <P0> AISI 1018 C.S. IS USED WHEN WELDED BODY CONNECTION ARE SPECIFIED.
6. 316 SS MANIFOLD/VALVE MEETS REQUIREMENTS OF NACE MR0175 (LATEST REV.) UP TO 140° F.

PGI RESERVES THE RIGHT TO CHANGE THE DESIGN, DIMENSIONS OR MATERIAL CONTENT OF OUR PRODUCTS WITHOUT PRIOR NOTIFICATION.

PGI INTERNATIONAL

16101 VALLEN DRIVE (713) 466-0056 or 1-800-231-0233
HOUSTON, TX. 77041 FAX: (713) 744-9892

**DOUBLE BLOCK AND BLEED
1/2" MNPT X 1/2" FNPT**

REVISION DATE	CAD#	DRAWING NO.	REVISION LEVEL
6-25-03	SCALE NONE	V-690S	9